

LEDON

LED Lamp A60 10.5W E27

The best option on the market to replace the most popular 60 W incandescent lamps: This lamp provides 800 lumens of beautiful light in a wide 270° beam angle. Its best-in-class color rendering of Ra 90 and warm white light color lets the true beauty and comfort of your home shine through.



| Item Description | Article Code | EAN Code | Dimmable |
|--|--------------|-----------------|--------------|
| LED LAMP A60 10.5W/M/927 E27 230V | 29001026 | 9 009453 006806 | No |
| LED LAMP A60 10.5W/M/927 E27 230V DIM | 29001027 | 9 009453 006851 | Yes |
| LED LAMP A60 10.5W/M/927 E27 230V D-CL | 29001028 | 9 009453 006905 | Double-Click |

General Characteristics

| | |
|----------------------------|---|
| Shape | A60 |
| Cap - Base | E27 |
| Finish | Matt |
| Energy Efficiency Label | A+ |
| Lamp materials | Plastic / Metal |
| Lifetime (hours) | 25 000 h |
| Lifetime (years) | 25 (burning time Ø 2.7 h per day) |
| Rated Lifetime | 25 000 h |
| Switching Cycles | 100 000 |
| Start Time from 0% to 100% | <0.5 s |
| Mercury Content | 0.0 mg |
| Lamp Recycling | Yes - please consider the local regulations |

Light Characteristics

| | |
|--|-------------------------|
| Nominal Luminous Flux | 800 lm |
| Rated Luminous Flux | 800 lm |
| Colour | Warm White |
| Colour Temperature | 2700 K |
| Colour Rendering Index | 90 |
| Lamp Efficacy | 77 lm/W |
| Lumen Maintenance Factor (at end of nominal lifetime) | 70 % |
| Beam Angle | 270° |
| Colour Consistency | <6 Step MacAdam Ellipse |
| Incandescent wattage equivalent suggested by LEDON | 75 W |
| Wattage equivalent according to Regulations (EC) 244/2009 & (EU) 1194/2012 | 60 W |
| Flicker Percent | < 3 % |

Electrical Characteristics

| | | | |
|----------------------------------|---------------------|-----------------|---------------------|
| Energy Consumption | 10.5 W | | |
| Rated Wattage | 10.5 W | | |
| Operating Frequency | 50/60 Hz | | |
| Supply Voltage | 230-240 V AC | | |
| | <i>Non-Dimmable</i> | <i>Dimmable</i> | <i>Double-Click</i> |
| Power Factor | >0.5 | 0.7 | 0.5 |
| Input Current (Measured Value) | 84 mA | 65 mA | 85 mA |
| Input Current (Calculated Value) | 46 mA | 46 mA | 46 mA |
| Inrush Current | 4.28 A | 6.15 A | 4.9 A |

Dimensions

| | | | |
|----------|--------|--------|--------|
| Height | 120 mm | 120 mm | 120 mm |
| Diameter | 60 mm | 60 mm | 60 mm |
| Weight | 138 g | 147 g | 147 g |

